



Test Report

No.452-20-A-0672

Date: November 17, 2020

1. Applicant

TOGAWA RUBBER CO.,LTD.

2. Accepted date

November 2, 2020

3. Sample

High Tear Silicone Rubber Sheet KK-125

4. Test method

Ministry of Health and Welfare Notice No.370, 1959

(Amendment: Ministry of Health and Welfare Notice No.85, 1986)

(Amendment: Ministry of Health, Labour and Welfare Notice No.595, 2012)

"Specifications, Standards and Testing Methods for Foodstuffs, Implements, Containers and Packaging, Toys, Detergents."

III. Implements, Containers, and Packaging

Material test method and elution test method of implements, container and packing made of rubber (except baby bottles) are shown in D-3 of III.

Material: Silicone rubber

Temperature used: above 100°C

(Continued on the following page)

5. Test result

Material tests

Test items		Results	Specification limits
Cadmium (Cd)	(μg/g)	Conformity (Less than 10)	100 or less
Lead (Pb)	(μg/g)	Conformity (Less than 10)	100 or less

Elution tests

Test items		Results	Specification limits
Phenol	(μg/mL)	Conformity (Less than 5)	5 or less
Formaldehyde		Conformity	The sample solution must not appear darker in color than the contrast solution.
Zinc (Zn)	(μg /mL)	Conformity (Less than 1)	15 or less
Heavy metal (as lead)	(μg/mL)	Conformity (Less than 1)	1 or less
Evaporation residue (20% ethanol)	(µg/mL)	Conformity (Less than 10)	60 or less
Evaporation residue (Water)	(μg/mL)	Conformity (Less than 10)	60 or less
Evaporation residue (4% acetic acid)	(μg/mL)	Conformity (Less than 10)	60 or less

6. Remarks

The above test results conform to Ministry of Health and Welfare Notice No.85, 1986 (Amendment: Ministry of Health, Labour and Welfare Notice No.595, 2012).

(End of report)

(No.452-20-1-0527)

Approved signatory: Ukai Ryota

(Ryota Ukai)

Section Chief of Section 2, CERI Osaka

Chemicals Evaluation and Research Institute, Japan

1-5-55, Aramotokita, Higashiosaka-shi, Osaka 577-0011, Japan

Tel +81-6-6744-2022

Fax +81-6-6744-2052